



Mobile Label Printer

P441B



- LCD screen, easy to operate
- Low noise, high quality, high speed printing
- 2500mAh large capacity battery, long standby
- TSPL, EPL, ZPL, DPL, CPCL, ESC/POS emulation compatible



P441B

Mobile Label Printer



QR CODE



EASY LOAD



COMPACT
DESIGN



HIGH SPEED

Printing		P441B	
Resolution	203 DPI		
Printing method	Direct Thermal		
Max.print speed	Max. 100mm (3.937") / s		
Max.print width	108 mm (4.25")		
Max.print length	1778 mm (70")		
Media			
Media type	Continuous, gap, black mark		
Media width	40 mm ~ 112 mm		
Media thickness	0.06 mm ~0.254 mm		
Paper roll diameter	50 mm		
Performance Features			
Processor	32-bit CPU		
Memory	8MB Flash Memory/ 8MB SDRAM		
Interface	Standard version: USB+Bluetooth Optional:USB+WIFI / NFC		
Screen	1.3"OLED		
Sensors	①Gap sensor ②Cover opening sensor ③Black mark sensor		
Performance Features			
Internal fonts	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software.		
1D bar code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on,MSI, PLESSEY, POSTNET, China POST		
2D bar code	PDF-417, Maxicode, DataMatrix, QR code		
Rotation	0°、 90°、 180°、 270°		
Emulaion	TSPL、 EPL、 ZPL、 DPL、 CPCL、 ESC/POS		
Physical Features			
Dimensions	150 mm (L) x 131 mm (W) x 64 mm (H)		
Weight	583 g		
Reliability			
Printer head life	30Km		
Software			
Operation system	Windwos / Linux / Mac / Android / iOS		
SDK	Windows / Android / iOS		
Power supply			
Input/Output	Input: AC 100-240V,0.5A 50-60Hz ; Output: DC 5V/ 2A		
Battery life	7.4V/2500mAh Li-Ion		
Options			
Optional accessories	Shoulder strap/Protection bag/Dual-slot battery charger/Vehicle Power Adaptor		
Environmental Conditions			
Operation environment	-10 ~ 45°C ,Humidity: 25 ~ 85% no condensing		
Storage environment	-40 ~ 60°C ,Humidity: 10 ~ 90% no condensing		